

AMSTRAD

VIRAAT

SUPER HEAVY DUTY

**HIGH
CAPACITY
MACHINE**

**POWERFUL
COOLING**

**5in1
CONVERTIBLE
COOLING**

**iFEEL
MODE**

**18.5*
metre
AIR
FLOW**

**4WAY
SWING**



— 1260 MM VIRAAT IDU —



*UNDER STANDARD INSTALLATION AND LAB TEST CONDITION

Powered by **INFRA.MARKET**

TECHNICAL SPECIFICATIONS OF VIRAAT SUPER HEAVY DUTY SPLIT INVERTER AIR CONDITIONERS

MODEL NAME		AMSi2731260ASHD	AMSi3031260ASHD
TYPE OF AC		INVERTER	INVERTER
		COOLING ONLY	COOLING ONLY
CAPACITY	TON	2.25T	2.5T
POWER SUPPLY SOURCE	V	230V/1PHASE/50HZ	230V/1PHASE/50HZ
COOLING CAPACITY (100%/50%)	W	8000 / 4000	8800 / 4400
MAX COOLING CAPACITY	W	8750	9600
INPUT POWER (100%/50%)	W	2550 / 805	2650 / 900
ANNUAL POWER CONSUMPTION	KW/H	1437.51	1552.96
ISEER (COOLING)	W/W	4.31	4.39
STAR RATING		3	3
VOLTAGE RANGE	V	150 ~290	150 ~290
RATED CURRENT	A	11.6A	12.8A
INDOOR UNIT			
NET DIMENSIONS (LXWXH)	MM	1260 X 362 X 280	1260 X 362 X 280
PACKING DIMENSIONS (LXWXH)	MM	1335 X 445 X 366	1335 X 445 X 366
WEIGHT (NET)/(GROSS)	KG	19.5 / 24.7	19.5 / 24.7
AIR FLOW VOLUME	M ³ /H	1550	1650
AIR THROW	MTR	18.5*	18.5*
OPERATING NOISE LEVEL	dB(A)	52	54
OUTDOOR UNIT			
SIZE	IN	20" WIDE	26"
REFRIGERANT	TYPE	R32	R32
NET DIMENSIONS (LXWXH)	MM	780 X 310 X 540	910 X 320 X 670
PACKING DIMENSIONS (LXWXH)	MM	918 X 405 X 593	1037 X 458 X 761
WEIGHT (NET)/(GROSS)	KG	25.8 / 29.8	41 / 45.9
OPERATING NOISE LEVEL	dB(A)	62	65
LIQUID TUBE DIAMETER	MM	1/4" (6.00MM)	3/8" (9.00MM)
GAS TUBE DIAMETER	MM	1/2" (12.00MM)	1/2" (12.00MM)

*UNDER STANDARD INSTALLATION AND LAB TEST CONDITION

AMSTRAD

Amstrad Consumer India Private Limited (formerly known as "OVOT Private Limited")

Gat No- 730, Milkat No 1660, Near Bolhai Mata Palace, Wade Bolhai, Taluka Haveli, Pune - 412207

Website: www.amstradworld.com | Email: care@amstradworld.com | Web App: app.amstradworld.com

Customer Care No.: 1860 266 7777 | IVR No.: 020 7197 0079 | WhatsApp Service Support: +91 9175950079

E-Waste Email: ewaste@amstradworld.com | E-Waste Toll Free No.: 1800 267 4777